

0800 500 484 Int: +64 9 828 3123 apexvalves.co.nz



Buy the Best!

# DIAPHRAGM RESERVOIR VALVE **COMBINED SINGLE & DUAL LEVEL**

### **APPLICATION**

- Pump fed large reservoirs It allows for a single level or variable minimum and maximum water levels.
- Mains/Gravity fed large storage tanks and/or reservoirs It allows for a single level or variable minimum and maximum water levels.
- Rain Harvesting as a back up water supply control valve, in the event of demand exceeding rainfall. (by clipping Weights together)

# **OPERATING PRINCIPLE**

The BigBoy® will be closed when both weights are submerged (maximum water level). The valve will remain closed until the bottom weight is exposed (minimum water level). The valve will then open and remain open until the maximum level is reached.

## **PRODUCT CODES**

BB32 - 32mm (11/4" BSP)

BB40 - 40mm (11/2" BSP)

BB50 - 50mm (2" BSP)

**RKBB** - Repair Kit

# **SPECIFICATIONS**


WORKING PRESSURE: 15kPa - 1200 kPa (2psi - 175psi)

Flow Rates:

Very high flow rates- Refer graph below Temperature range: 1° - 60°C (34°F-140°F)



- Watermark approved
- New Zealand patent No. 598546
- New Zealand patent No. 328862,
- New Zealand patent No. 535912
- Australian patent No. 736446,
- RSA patent No.98/87777,
- Australian CLASS 11, No. 1025211





MANUFACTURED BY: ALVES

0800 500 484

**HYDROFLÔW** Rosebank Road, Ackland, New Zealand apexvalves.co.nz

North Island P.O. Box 33780, Takapuna, Auckland. Ph: 09-415 5585 Fax 09-415 6150

DISTRIBUTED BY:

P.O. Box 4419, Christchurch. Ph: 03-341 1048 Fax 03-341 1098 hydroflow.co.nz



Overflox

NORMA Pacific Pty. Ltd 85 Merrindale Drive Croydon South VIC 3136, AUSTRALIA Tel +61 3 9761 4416 Fax +61 3 9761 4030 www.normagroup.com



NZ MADE

Buy the Best!