

APPLICATIONS

Grundfos pressure tanks are for cold water and are ideally suited and approved for use with drinking water.

The range assures reliable supply in both domestic and industrial situations.

FEATURES

- Potable water application
- Can be used with any Grundfos pump
- Five year warranty
- Tank capacity up to 450 litres on request
- Water Mark approved*

CONSTRUCTION

- The tanks have a non-toxic butyl rubber diaphragm, dividing the tank chamber in two compartments. The upper compartment contains compressed atmospheric air. The lower compartment has a liner in polypropylene (PP) and is filled with water from the pump
- Vertical installation
- Pre-charge pressure: 150 kPa / 22 psi

Note: the tank pressure must be checked at least twice a year. Set the tank pressure 10% below the pump cut-in pressure



TECHNICAL FEATURES

Tanks	Capacity (litres)	Water temp (°C)	Max Operating pressure (kpa)	Mounting type	Connection inlet	Dimensions (mm)		Weight (kg)
						D	H	
GT-H-8*	8	0/90	1000	Pipe	1”M	202	303	2.3
GT-H-18*	18	0/90	1000	Pipe	1”M	279	367	4.6
GT-H-60*	60	0/90	1000	Foot	1”F	388	528	10
GT-D-100*	80	0/90	1000	Foot	1”F	397	755	16
GT-C 80 PN8.6 Composite	80	0/90	860	Foot	25 mm	418	852	11
GT-C 130 PN8.6 Composite	130	0/90	860	Foot	25 mm	418	1227	15
GT-C 250 PN8.6 Composite	250	0/90	860	Foot	1 ¼”F	542	1303	26



DIMENSIONS / INSTALLATION

