

Product Specification

API - Spin Clean Filters

Applications:

High quality screen filter for agriculture and landscape irrigation systems.

Specification:

AG Products "Spin Clean™" filters are unique in that incoming dirty water is forced through a directional nozzle plate onto the inside of the stainless steel screen. This creates a centrifugal action which rotates debris down he screen wall to the large debris holding basin. Debris is flushed out via a ball valve or unscrewing cap. Spinning action keeps more of the screen area clean, minimizing pressure losses due to excessive dirt build-up.



4E20-50

Features:

207 BANNISTER ROAD CANNING VALE WESTERN AUSTRALIA 6155 PHONE: (08) 9455 1677 TOLL FREE: 1 800 998 037

hrproducts@bigpond.com

www.hrproducts.com.au

E-MAIL

PERTH

WEB SITE

ADELAIDE Cnr WILSON ST & FREDERICK RD ROYAL PARK SOUTH AUSTRALIA 5014 PHONE: (08) 8341 0008 TOLL FREE: 1 800 888 125

BRISBANE

14-16 TOLMER PLACE SPRINGWOOD QUEENSLAND 4127 PHONE: (07) 3290 1200 TOLL FREE:1 800 777 325

SYDNEY 11-13 SAMMUT STREET SMITHFIELD NSW 2164 PHONE: (02) 9725 5733 TOLL FREE: 1 800 251 945

MELBOURNE

Cnr Waterdale Rd & Vernon Ave HEIDELBERG HEIGHTS VICTORIA 3081 PHONE: (03) 9457 7500 TOLL FREE: 1 800 331 168


MACKAY MOBILE: 0418 742 144

COBRAM MOBILE: 0417 054 475

NEWCASTLE MOBILE: 0418 292 769

DUBBO MOBILE: 0409 489 092 • 20mm and 25mm inlet/outlet

- Two piece threaded housing with 'O' ring seal.
- Molded from high heat and chemical resistant ABS plastic.
- Ball valve for flushing debris.
- Stainless steel filter screen.
- 20mm screen area 585mm
- 25mm screen area 710mm
- 20mm maximum size cleaning efficiency 15LPM
- 25mm maximum size cleaning efficiency 26LPM
- Maximum operating pressure 550kPA
- Mesh selection 50, 100, 150
- 20mm maximum flow 42LPM
- 25mm maximum flow 105LPM



4E25-50

Description	Code
20mm Spin Clean Filter	4E20-XXX
25mm Spin Clean Filter	4E25-XXX
*	

Specify mesh size when ordering



