

Hydro-Cyclonic In-Line Filter 40mm (1½") & 50mm (2")

Application:

Filter suitable for filtration of sand and inorganic particles on drip, micro jets and sprinklers.

Incoming dirty water is forced through a directional nozzle plate onto the inside of the stainless steel filter screen. This centrifugal motion and gravity move the debris downward and out the flushing valve. Periodical opening of the flush valve will release the dirt from the debris area without the need to open the filter for cleaning, thus the filter is kept cleaner for a longer period



Complete glass reinforced polypropylene construction makes the filter durable to time, solar radiation and chemicals.

Screen Surface Area: 40mm (1½") 185cm²
 50mm (2") 274cm²

Discharge: 40mm (1½") 133 lpm
 50mm (2") 266 lpm

Working pressure 800kpa

Body: PPC, Screen: INOX.

MODELS	CODE
40mm Filter with 120 mesh	HR3388-40
60 mesh element suits HR3388-40 (Grey)	HR338840-60M
80 mesh element suits HR3388-40 (Black)	HR338840-80M
120 mesh element suits HR3388-40 (Red)	HR338840-120M
150 mesh element suits HR3388-40 (Brown)	HR338840-150M
50mm Filter with 120 mesh	HR3388-50
60 mesh element suits HR3388-50 (Grey)	HR338850-60M
80 mesh element suits HR3388-50 (Black)	HR338850-80M
120 mesh element suits HR3388-50 (Red)	HR338850-120
150 mesh element suits HR3388-50 (Brown)	HR338850-150

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE – PRODUCT DRAWINGS / IMAAGES ARE REPRESENTATIVE ONLY AND ARE SUBJECT TO CHANGE.

PERTH

PH: 08 9455 1677
 FAX: 08 9455 1680
hrrsales@hrproducts.com.au

SYDNEY

PH: 02 9725 5733
 FAX: 02 725 5283
infonsw@hrproducts.com.au

MELBOURNE

PH: 03 9457 7500
 FAX: 03 9457 7400
infovic@hrproducts.com.au

BRISBANE

PH: 07 3806 0522
 FAX: 07 3806 0533
infoqld@hrproducts.com.au

ADELAIDE

PH: 08 8341 0008
 FAX: 08 8341 0707
infosa@hrproducts.com.au