







Softrol™ Cabinet Dimensions

| Α | 105 mm | |
|---|---------|--|
| В | 75 mm | |
| С | 105 mm | |
| D | 953 mm | |
| E | 1125 mm | |
| F | 285 mm | |
| G | 490 mm | |
| | | |







GENERAL INFO DOMESTIC WATER SOFTENERS

The Softrol™ SOL-E1 Automatic Timer water softening systems requires less maintenance than the semi-auto systems. After the initial installation simply set the times and dates requiring backwash and the unit regenerates automatically.

SYSTEM SPECIFICATIONS AND PERFORMANCE DATA

| Available Models: | SOL30-E1 | SOL40-E1 |
|--------------------|-----------------|-----------------|
| Size of Residence: | Small to Medium | Medium to Large |
| Service Flow Rate: | 30 lpm | 40 lpm |
| Maximum Flow Rate: | 100 lpm | 100 lpm |
| Maximum Pressure: | 825 kPa | |
| Capacity: | 12,000 litres^ | 18,000 litres^ |
| Connection: | 25 mm M [1" M] | |
| Drain: | 15mm M | |
| Power Required: | 240V | |

[^]Based on a hardness of 130ppm

FEATURES & BENEFITS

- Regenerates automatically.
- \cdot 1-99 day timer controller.
- 10 selectable programmed cycles.
- 12 volt transformer.
- Reliable, durable and simple.
- WaterMark Certified (License No. WM 74953).
- 6 Year Platinum Protection.



WHOLEHOUSE PROTECTION

These systems provide peace-of-mind water softening throughout the house. You'll notice benefits all through the house. Soap and shampoo's will lather better, your skin will not be as dry, and soap scum will be reduced. Clothes are softer and hot water appliances will last many more years.

EASY TO MAINTAIN, SET AND FORGET

The Puretec SOL-E1 Series systems uses an E1-Matic™ valve that backwashes automatically on a preset time. After the initial installation, simply set the times and dates requiring backwash and the unit automatically regenerates. Power usage is extremely low, similar to that of a garden watering system.

HOW IT WORKS

- 1. Untreated water passes through water softening resin.
- 2. Resin softens water by reducing ions such as calcium and magnesium.
- 3. Soft water enters your home, providing cleaner laundry, softer skin, easier cleaning, as well as soap, energy, and appliance savings.
- 4. The system uses a salt (brine) solution to clean and recharge the resin, while releasing hardness down the drain.

A. Control Valve B. Inlet C. Outlet ntreated Water rine Tank

NEW FEATURES



Sliding water proof cover

Ergonomic cover for easy maintenance with the new sliding cover.



Easy access controller

Easy access to the controller for programming and maintenance.



Salt Chute

Effortless salt refilling