

Specifications

All Colard Diesel models are speed governed at approx 3100 RPM.

At this speed the pump will not overload the engine under a variety of pumping conditions unless exceeding water flow rates.

The Diesel engine is made in Southeast Asia and imported to Australia where it is re-branded.

10HP Colard Pumpset & Roll frame overall dimensions :
Length 650mm, Width 490mm, Height 725mm

Model	Colard 10 HP (Diesel Engine only)
Type	Single-Cylinder, Vertical 4-Cycle, Air-cooled Diesel
Combustion System	Direct Injection
Displacement [cc(cu.in.)]	418 (25.51)
Bore x Stroke [mm (in.)]	86×72 (3.39×2.83)
Rated Speed [rpm]	Governed (3100)
Power Take Off	Crankshaft
Starting System	Recoil or Recoil/Electric
Fuel Tank Capacity	12 Litres (Long Range Tank)
Lub. Oil Capacity	1.65 Litres
Fuel Consumption (approx)	280 - 305 grams/KWh = 2.417 Litres per hour
Dimension: L x W x H [mm(in.)]	417(16.42) x 470(18.50) x 494(19.45)
Dry Weight(Recoil) [kg(lbs.)]	48 Kg (106)
Dry Weight(Electric) [kg(lbs.)]	53 Kg (117)

E: Electric Starter

